



WATER INFRASTRUCTURE Conference

October 13-16, 2015
Bethesda, Maryland
Relevant | Smart | New



CFRP Repair of Pipelines – The Current State of the Art

Murat Engindeniz, Ph.D., P.E.

SIMPSON GUMPERTZ & HEGER



Engineering of Structures
and Building Enclosures

mengindeniz@sgh.com

(781) 907-9110



CFRP Repair of Pipe

- + Widely preferred method
- + No excavation
- + Standalone
- + Fast
- + Targeted or continuous repairs
- + Emergency repairs
- Specialty repair in confined space
- Environmental controls
- Cost



10/14/2015

History


- 1980s: CFRP is used to repair civil infrastructure
- 1990s – early 2000s: Various utilities start using CFRP to repair pipe
- Mid-2000s: CFRP repair of pipe is widespread
- 2009: AWWA Concrete Pressure Pipe Committee appoints a subcommittee
- 2011: AWWA Standards Council approved the development of a standard
- 2011: Water Research Foundation awards the first research project to form the technical basis of the standard
- 2013 – 2015: Additional research on watertightness, degree of cure, etc.
- 2015: AWWA Draft Standard for CFRP Renewal and Strengthening of PCCP is complete (currently balloted)

10/14/2015

Earlier Practice (1990s-2000s)

- “Factor of safety” design
- Few limit states (i.e., mostly pressure, Pr/t)
- Few CFRP layers, sometimes with no longitudinal
- CFRP terminated mostly on concrete
- No watertightness measures
- Limited QA inspections and testing
- Limited requirements to qualify material, contractor, designer, inspector

Earlier Practice (1990s-2000s)





10/14/2015

Practice in 2000s

- Need for better termination is established
- Additional limit states are considered
- Standalone concept
- More CFRP layers
- Improved QA/QC requirements


Practice in 2000s



10/14/2015

WERF Projects (2011-2015)

- LRFD procedure
- FEA of CFRP-lined pipe
- Full-scale tests
 - Hydrostatic pressure
 - Three-edge bearing
- Laboratory tests
 - Shear bond strength
 - Degree of cure
 - Watertightness



10/14/2015

LRFD Approach

$$R_u \leq \lambda\phi R_n = \lambda\phi(CR_o)$$

- R_u = required strength computed from factored load combinations
- λ = time effect factor
- ϕ = resistance factor
- R_n = strength in the end-use condition
- C = material adjustment factor
- R_o = test strength of unexposed material

10/14/2015


Limit States

- Hoop rupture under pressure
- Hoop rupture in bending
- Hoop rupture under combined pressure and bending
- Hoop buckling
- Longitudinal rupture in tension
- Longitudinal rupture at BWZ edge
- Longitudinal buckling
- Shear debonding at pipe ends


10/14/2015

FEA Validation

Sequential analysis of buried CFRP-lined pipe that continues to degrade



Buckling analysis



Full-Scale 3-Edge Bearing Tests

48 in. LCP - Control



48 in. LCP



54 in. ECP



10/14/2015

Full-Scale Hydrostatic Pressure Tests

54 in.
ECP



48 in.
LCP



10/14/2015

Shear Bond Strength on Steel Substrate



Cleaning with acetone



Cleaning with wirewheel



Grinding



Sandblasting to SSPC SP-10 near-white finish





Sandblasting to SSPC SP-5 white finish




10/14/2015

Degree of Cure



10/14/2015

Degree of Cure vs Material Properties




Need minimum 85% cure before placing pipe back in service

Cure Level	No. of Samples	Mean Strength (ksi)	Mean Modulus (ksi)	Mean Ultimate Strain (%)
75% (24 hr at 70°F)	12	91.3	₍₁₎	₍₁₎
88% (72 hr at 70°F)	12 ⁽²⁾	163.1	12,100	1.32%
95% (24 hr at 70°F + 16 hr at 100°F)	12	145.4	11,800	1.23%
100% (69 hr at 70°F + 3 hr at 165°F)	12	144.9	12,300	1.18%

10/14/2015


Progression of Cure

Varies by material



10/14/2015

How to Verify Cure in Construction



Take samples in field



10/14/2015

Send to laboratory




Data logger to monitor temperature and RH during shipment to laboratory

Thickened epoxy samples chipped out from pipe surface

Test (DSC)




Determine degree of cure



The Latest Development: Watertightness Test


- Will standalone CFRP remain watertight at design pressure?
- Watertightness is affected by:
 - Saturation
 - Laminate architecture
 - Brittleness of resin
 - Degree of cure
 - Top coat



10/14/2015

The Latest Development: Watertightness Test

- Allows testing of laminates on a project-by-project basis
- Allows proof-of-concept tests at reasonable cost
 - New fabrics, resins, top coats
- 500 psi capacity



10/14/2015

Watertightness Acceptance Criteria

- $P_{WLT} = \min(P_{test1}, P_{test2}, P_{test3}, \dots)$
- $P_{WLT} > 2P_{design}$

Specimen with no leaks at 400 psi



Specimen with multiple leaks at 150 psi



10/14/2015

Summary of Current Practice

- Qualification of designers, materials, contractors, inspectors
- LRFD design per AWWA Standard
 - Consistent design with solid experimental and analytical basis
- Varying laminate architectures
- Watertightness measures
- More layers now? – yes and no
- Improved QA procedures (e.g., cure)

10/14/2015

Closure

- CFRP repair of pipe is a well-established technology.
- As with other technologies, it has evolved over the years.
- A standard has been developed, which will result in more consistent design and installation.
- Moving forward, methodologies are not expected to change significantly.
- Focus may be shifted to new CFRP lining methods, materials, reducing cost, etc.

Acknowledgement

- Water Research Foundation
- American Concrete Pressure Pipe Association
- Hanson Pipe and Products
- Tarrant Regional Water District
- Metropolitan Water District of Southern California
- Howard County Department of Public Works
- Washington Suburban Sanitary Commission
- Structural Technologies
- Fyfe Company
- Fibrwrap Construction

10/14/2015

Questions?

Murat Engindeniz, Ph.D., P.E.
mengindeniz@sgh.com
(781) 907-9110

SIMPSON GUMPERTZ & HEGER



Engineering of Structures
and Building Enclosures